The design of the church, which was developed to create an alternative place of worship following the structural damage of the historic building caused by the 2012 earthquake, is based on the concepts of modularity, flexibility, versatility, ease of execution and containment of construction and running costs. The project concept builds on the idea of assembling several timber modular units the shape of which was subsequently modelled in relation to the needs of the site and the local community, with a high level of attention paid to the architectural and liturgical aspects.

Composition of the timber church

The design project comprises a nave area composed of a single space. The internal height is 3 m for the side aisles (areas of worship) and approximately 6 m for the central nave. The entrance to the church has four doors facing different directions, symbolising a crossroads and meeting place. A large glazed area on the north face fills the interior of the building with natural light so artificial lighting is unnecessary during the hours of daylight: the window also offers a view of the bell tower of the historic church this creating a sense of continuity between the old and the new. The building thus communicates with the surrounding environment by means of the access routes, the key prospects and the reduced volumes of the architectural space.

A flexible timber construction suitable for future functional transformations


The design solution of creating a flexible structure is perfectly compatible with the idea of a temporary building designed to replace the traditional place of worship for the time required to repair the damaged historic church. Once the damaged church has been repaired, the temporary building can be used for alternative uses related to parish activities. The simplicity of composition, thanks to the construction technology employed utilising timber elements, is compatible with the differentiation of functions, spaces and distribution paths and with the building's flexibility of use.

PRODUCT SPECIFICATION

Timber church			
Localization: Renazzo (Ferrara)			
Intended use: Churches and places of worship			
Architetural and structural design: Architect Barbara Fiorini Architect Claudia Manenti Architect Maurizio Martinuzzi Engineer Luca Venturi			
Total area: 450ft			
nage not found or type unknown	hage not found of type unknown	nage not found or type urknown	l mage not found of type unknown
mage not found of type unknown			

BUILDING SYSTEM

XLAM




Reasons for choosing the Xlam system

The Xlam system is a technical innovation in the construction of timber homes and buildings. The system's exceptional versatility allows the creation of a wide range of architectural constructions, including multi-storey timber buildings. The system assures optimal thermal insulation and a high level of fire resistance, a fast drying process and exceptional acoustic insulation.

About the Xlam system

The Xlam panel is composed of crossed layers bonded together, making the construction system extremely versatile. Composed of 99.4% timber and 0.6% adhesives, Xlam is considered to be a monolithic material capable of supporting very high loads and withstanding external stresses and seismic activity.



Sede / Headquarter:

Sistem Costruzioni s.r.l. Via Montegrappa 18 - 20 41014 Solignano di Castelvetro (MO), Italy Tel. +39 059 797477 - 797591 Fax. +39 059 797646

info@sistem.it www.sistem.it

Sucursal Cuba

Centro de Negocios Miramar Calle 3a e/e 76 y 78, Edificio Beijing, Piso 1, Oficina 133 Ciudad de la Habana, Cuba Tel. 0053 7 2040823

sistemcuba@enet.cu www.sistem.it